

|                                       |                           |
|---------------------------------------|---------------------------|
| Part Number                           | VN-HC4x4-0738-500W-OP-xxx |
| Operating Frequency ( MHz )           | 698-3800                  |
| Impedance ( Ohm )                     | 50                        |
| VSWR                                  | 1.3                       |
| Coupling (dB)                         | 6.1                       |
| Insertion Loss (dB)                   | ±1.5                      |
| Isolation (dB)                        | 23                        |
| IM3 (dBc @ 2×43dBm)@xxx               | -150/-160/-165            |
| Application                           | Indoor & Outdoor          |
| Degree of Protection                  | IP65                      |
| Operating Temperature ( °C )          | -40 ~ + 80                |
| Interface                             | 4.3-10 Female             |
| Handling Power (Watt, max)            | 500                       |
| Peak Power (Watt, max)                | 1500                      |
| Dimension (mm)(L×W×H, excl connector) | 234.6X102X54              |
| Net Weight (g)                        | 2580                      |
| Packing Dimensions (mm,L×W×H)         | 305X170X115               |
| Packing Carton Size (mm,L×W×H)        | 620X370X190               |
| ROHS Compliance                       | Yes                       |
| Revision                              | R1                        |
| Date                                  | 01-August -2022           |

